



# DINGO™ 950



## SPECIFICATIONS

General Specifications  
(without operator and without attachments)

All Dingo 950 models have the same outside dimensions/Chassis.

(Approximate Only)

Overall width	840mm-1050mm
Overall length (without attachment)	1565mm
Overall height	1200mm
Maximum Operating Height (with standard bucket)	2080mm
Operating Weight	700-800kg
Turning radius with standard bucket	1300mm
Rated lift capacity - bucket (with 90kg operator)	250kg
(lifting capacity up to 500 kg with certain attachments)	
Speed	0→6 km/hr
Angle of departure	20°
Engine HP	20-22 HP
Wheel motor sizes	29 cu in
Wheel base	710-800mm
Drive Chain	ASA 60H (Heavy Link 3/4")
Ground clearance	135mm
Tyre size	18 x 8.50 x 8 (4 ply) std
Hydraulics	2 pump
Pump sizes	9 & 3 cc
System relief pressure (hydraulic)	3000psi (206 Bar)
Hydraulic Reservoir capacity	60 litres
Hydraulic Output	43 litres per minute
Filtration	25 micron
Standard bucket capacity	0.11 cu m
Standard bucket dump height	1240mm
Reach fully raised standard bucket	600 mm
4 in 1 bucket capacity	0.11 cu m
4 in 1 bucket dump height	1750mm
Reach fully raised 4 in 1 bucket	600 mm
Chipbark bucket capacity	0.18 cu m
Height to hinge pin(std bkt in highest position)	1680mm

Specifications and design subject to change without notice.

